



Aluminum Camera housing & Bracket

[Features]

- Aluminum chassis
- Completely weather resistant
- Protects your valuable camera investments

[Application & Benefits]

The D-i3-6800 is a light duty wall mount camera housing designed specifically for use with any of the i3's camera series. Manufactured from die cast aluminum, the D-i3-6800 is capable of supporting a maximum load of 20 pounds (9 kg) and can be safely mounted to any vertical load-bearing surface. D-i3-6800 is beige color and IP66.

D-i3-6800 camera enclosure is constructed from die cast and extruded aluminum without heater and blower while its counter part D-i3-6800-HB does. The D-i3-6800 has a lower body length of 16 inches. The front hinged lid provides easy access to the removable camera sled. Two adjustable (PG13.5) glands on the bottom of the enclosure allow for easy installation of the power and video cables. The rear link-lock latch can be used with a padlock of suitable size to secure the enclosure.

The D-i3-6800-HB (heater and blower) does require 24AC and less than 1AMP. It is used for outdoor while the D-i3-6800 is indoor housing.

[Specifications]

- Weight (bracket and housing): 1.56kg or 3.45lbs
- Dimension (LxWxD): 413x250x119 mm / 16x5.75x4.25 inch
- Camera bracket length: 286 mm or 11.25 inches



©2009 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice. This data sheet may not be reproduced without permission.